



SILICON CARBIDE

220 Crystolon Lapping Compound

IDENTITY INFORMATION

This product consists of silicon carbide powder mixed in an oil-soap base which is comprised of hydrocarbon oils, vegetable oils, and animal fatty acid soap. Solids content is approximately 30%. Contains less than 50 ppm leachable chlorides.

PHYSICAL PROPERTIES

Specific Gravity (H ₂ O = 1)	.9, approximate
Melting Point	110°F
Evaporation Rate (Butyl Acetate = 1)	Negligible
Boiling Point	N/A
Vapor Pressure (mm Hg.)	Negligible
Vapor Density (AIR = 1)	Greater than air.
Solubility in Water	No
Appearance and Color	Grey paste, slight oily odor.

FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	375°F, actual test
Flammable Limits	
LEL	N/A
UEL	N/A
Extinguishing Method	CO ₂ or foam. Do not use water.
Special Fire Fighting Procedures	Treat as oil fire.
Unusual Fire and Explosion Hazards	None

UNITED STATES PRODUCTS CO.

518 Melwood Ave. • Pittsburgh, PA 15213-1136 • Phone: 412-621-2130 • Fax: 412-621-8740

Web Site: www.us-products.com

OSHA 174, September 1985

Data Prepared • May 2006